

# INTERLUBE IL-RDF150

BIODEGRADABLE LUBRICANT FOR PNEUMATIC DRILLS

IL-RDF150

## DESCRIPTION :

The biodegradable lubricants RDF150 are products formulated from easily biodegradable renewable resources and designed to provide maximum protection to pneumatic and surface drills. These oils are formulated from high viscosity vegetable oils and anti-wear, anticorrosion, and extreme pressure additives. RDF150 lubricants offer excellent thermal and oxidative stability and reduce service temperature to ensure superior performance and minimal impact on the environment. RDF lubricants are available in different viscosity grades.

## CHARACTERISTICS :

- Easily biodegradable
- Superior protection against wear and extreme pressures
- Good corrosion protection
- High flash point
- Ashless, good adhesion and low odor
- Reduces friction and heat

### INTERLUBE IL-RDF150

| Product Code                     | Test Method      | IL-RDF150  |
|----------------------------------|------------------|------------|
| Density                          | ASTM D1298       | 0.91       |
| Viscosity @40°C, cSt             | ASTM D-445       | 100        |
| Viscosity @ 100°C, cSt           | ASTM D-445       | 9.6        |
| Viscosity Index                  | ASTM D2270       | >220       |
| Pour Point °F(°C)                | ASTM D97         | -30(-34)   |
| Flash Point °F(°C)               | ASTM D92         | >600 (315) |
| Copper Blade Corrosion           | ASTM D4048       | 1A         |
| Rust test A & B                  | ASTM D1743       | SUCCESS    |
| Biodegradability OECD 301B, %    |                  | >75        |
| Timken Load                      | ASTM D2509 (LBS) | >60        |
| Falex EP load carrying capacity. | ASTM D3233       | 3500       |
| Adhesive property.               |                  | YES        |

**PACAKGING :** 18.9 L PAIL.